

# DuploCOLL® 3720

Double-sided adhesive tape with special paper carrier for universal applications

## Product construction

	Name	Colour	Thickness [mm]
Liner	Silicone paper	yellow	approx. 0,08
Adhesive covered side	Modified acrylic		
Carrier	Special paper	white	approx. 0,13
Adhesive open side	Modified acrylic		
<b>Total thickness:</b>			approx. 0,21

## Product advantages

- High initial and final adhesion
- Excellent resistance to ageing, weathering and UV-radiation
- Far-reaching resistance to the influence of chemicals and solvents
- The consistency of the adhesive guarantees excellent wetting of the substrate, enabling its use on highly absorbent surfaces such as textile, leather and paper.

## Main application fields

- Self-adhesive preparation of polyethylene, PVC and polyurethane foams
- Splicing of paper, textiles, plastics and metal foils
- Bonding of leather, felt and cork
- Fastening of signs, face plates, holders and front covers

## Product features

## Applicability on

Initial adhesion	● ● ●	Foam	● ● ○
Final adhesion	● ● ○	Rubber	● ● ○
Dimensional stability	● ○ ○	Fabric	● ● ●
Adhesion on even surfaces	● ● ●	Glass/Ceramics	● ● ○
Adhesion on rough surfaces	● ● ○	Wood	● ● ●
Ageing resistance	● ● ●	High energy plastics: PVC, PC, ABS,...	● ● ●
Weathering resistance	● ● ●	Low energy plastics: PE, PP,...	● ● ○
Chemical resistance	● ● ●	Metal	● ● ●
Resistance to plasticizers	● ● ○	Paper/Cardboard	● ● ●

● ● ● very suitable    ● ● ○ suitable    ● ○ ○ suitable with reductions    ○ ○ ○ not suitable


# DuploCOLL® 3720

Double-sided adhesive tape with special paper carrier for universal applications

## Specific technical data\*

Temperature range	-40 °C to +150 °C**
Peel strength on polypropylene after 24 h at room temperature	21 N/25 mm
Peel strength on polyethylene after 24 h at room temperature	17 N/25 mm
Certified and recognized according to UL 969 	

## Technical Data

Shear strength	on stainless steel at +23 °C +/- 2°C	40 N/625 mm <sup>2</sup>	
Peel strength 180°	on stainless steel at +23 °C +/- 2°C	30 N/25 mm	

## Application

Recommended application temperature	18 °C to 35 °C
Application guidelines	<a href="http://www.lohmann-tapes.com">www.lohmann-tapes.com</a>

## Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).  
The storage stability is one year after delivery.

## Product presentation

Converted product	Rolls			Spools		
Width [mm]	> 6	> 15	> 19	on request		
Length [m]	50/100	200	300			
Max. log width: 1260 mm	Other dimensions, die-cuts and sheets on request.					

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

\* Specific test results, statistically not approved.

\*\* Reached temperature in a rising heat test.

# DuploCOLL® 3720

**Double-sided adhesive tape with special paper carrier for universal applications**

## **IMPORTANT NOTE**

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: July 2017

Lohmann GmbH & Co. KG  
Irlicher Strasse 55  
56567 Neuwied  
Germany  
Phone: + 49 (0) 26 31 34 - 0  
Fax: + 49 (0) 26 31 34 - 6661  
E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

